



B.S. SRL - BADERNE SPECIALI -

VIA G.MARCONI N.11/H 24060 CREDARO (BG)
TEL. E FAX: 035/93.55.54

PACKING SHEET

ART. 700

Denomination: RAMIE' with teflon and lubricant

TYPE: *Diagonally braided from natural Ramie fibre, densely impregnated with a PTFE-compound, lubricated. The packing combines good elasticity and flexibility with a low coefficient of friction.*

APPLICATIONS: *Very versatile packing for rotary and reciprocating pumps, also suitable for valves. Can be used in many different industries for insensitive applications including the pulp and paper, marine and food industry. Because Ramie does not rot or decompose, is an excellent packing for stern glands and rudder post glands. Cold and hot water, hydrous solutions containing solids, cellulose slurry, brine, oils, greases, etc.*

NOT SUITABLE FOR: *Acids and high concentrated lyes, oxygen.*

TEMPERATURE	-temp.	+ temp	
(°C)		+ 130	
PRESSURE	rot.	alt.	stat.
(BAR)	20	20	30
STEAM			
INERT GAS		—	
Ph		5 - 11	
DENSITY		1,5	
SPEEDNESS m/s		10	

B.S. SRL - BADERNE SPECIALI -
VIA G.MARCONI N°11/H 24060 CREDARO (BG)